

Aluminum 7075-T6 Technical Datasheet

Key Features

Excellent strength

Common Applications

- Aircraft fittings
- Gear and shafts
- Fuse parts
- Missile parts
- Regulating valve parts
- Worm gears
- Aerospace and defense applications

Material Description

Aluminum 7075-T6 is a high-strength alloy renowned for its exceptional mechanical properties and excellent machinability. The "T6" designation indicates that the material has been solution heat-treated and artificially aged to achieve the T6 temper, which provides the highest mechanical strength among all temper conditions. The material is widely used in aerospace and aviation applications, including aircraft structural components, fuselage frames, and wing structures, due to its outstanding strength-to-weight ratio and fatigue resistance. It is also utilized in high-performance applications requiring lightweight materials with superior mechanical properties, such as bicycle frames, automotive components, and firearm parts.

Chemical Composition (%)										
	Al	Cr	Cu	Fe	Mg	Mn	Si	Ti	Zn	
Min.	87.1	0.18	1.2		2.1				5.1	
Max.	91.4	0.28	2.0	0.50	2.9	0.30	0.40	0.20	6.1	

Mechanical Properties

Ultimate Tensile Strength	;
Tensile Yield Strength	-
Hardness	I
Elongation at Break	9

83,000 PSI 73,000 PSI Rockwell B87 9%

Physical Properties

0.102 lb/in³ (2.81 g/cm³) 130W/m.K 10,400 KSI (71.7 GPa) 890 - 1,175°F (477 - 635.0 °C)

Technical Assistance

Our knowledgeable staff, supported by our in-house team of expert metallurgists and engineers, is ready to assist you with any technical inquiries.

InstaVoxel[™] - On-Demand Manufacturing Expert

859 Willard Street Suite 400, Quincy MA 02169 USA +1 (617) 302-1629 | info@instavoxel.com www.instavoxel.com



InstaVoxel's quality control system is ISO-9001 certified, and all our partners hold relevant certifications.



All information in our data sheet is based on approximate testing and provided to the best of our knowledge and belief. It is presented without any contractual obligations and does not constitute a guarantee of properties, processing, or application possibilities in specific cases. Our warranties and liabilities are defined solely by our terms of trade.